



YB 13-015 RE - Red PE protection tape

Description	A strong and conformable red polyethylene film tape coated with a specially formulated, high tack, removable acrylic adhesive system.
Product properties	This product has excellent ultra violet resistance and resistance to moisture, acids, chemicals, alkalis, oils, abrasion, and weathering. Good adhesion on rough and uneven substrates.
Specifications	Is lmds registered
Applications	Primarily used as a masking tape for stucco application but may also be used as a weather seal for applying plastic storm windows, film can sealing, ink container sealing, and poly sheeting where adhesive removability is desired. Surface protection of glazed and printed surfaces. All applications where there is a need for excellent longterm protection on smooth and rough substrates in building, automotive and aerospace industries
Storage and ageing	1 year shelf life whilst stored in original packaging and ambient room temperature. Keep out of direct sunlight.
Applying tips	All substrates should be clean and contamination free, a solvent such as Isopropyl-Alcohol is recommended for cleaning purposes, and the tape should be applied with pressure.

TECHNICAL DATA

Carrier	PE film	
Adhesive	Acrylic pure	
Colour	Red	
Weather resistant	Yes	
UV resistant	Yes	
Plasticizer resistant	Yes	
Ageing resistant	Yes	
Thickness Carrier	0,12 mm	4,72 Mils
Thickness Total	0,15 mm	5,91 Mils
Adhesion on stainless steel	6 N/25mm	1,37 Lbs/inch
Static shear 23°C	1 kg/625mm ²	2,28 Lb/inch ²
Tensile strength length	55 N/25mm	12,6 Lbs/inch
Elongation length	250 %	
Temperature performance (short time)	90 °C	194 °F
Service temperature	Between -40 and 80 °C	Between -40 and 176 °F
Application temperature	Minimum 0 °C	Minimum 32 °F

Disclaimer: Values shown above are averages. See our delivery conditions which apply. Each user should make his own test to determine the product suitability for his intended use and shall assume all risks and liability in connection therewith. Stokvis Tapes' is not liable for any damages resulting of non suitability of the product. Many factors beyond Stokvis Tapes' control can affect the use and performance of the product in a particular application, including the conditions under which the product is used and the time and environmental conditions in which the product is expected to perform. Since these factors are uniquely within the user's knowledge and control, it is essential that the user evaluates the Stokvis Tapes' product to determine whether it is fit for a particular purpose and suitable for the user's method of application.

Stokvis Tapes Poland
ul. Energetyczna 6
80-180 Kowale
+48 (0) 58 762 31 31
+48 (0) 58 762 31 30